



Power Segment			
Pin NO.	Type	Name	Type
P1	V33	P9	V5
P2	V33	P10	Ground
P3	V33	P11	Ready Lead
P4	Ground	P12	Ground
P5	Ground	P13	V12
P6	Ground	P14	V12
P7	V5	P15	V12
P8	V5		

Signal Segment			
Pin NO.	Type	Name	Type
S1	Signal Ground	S8	Signal Ground
S2	TP+	S9	TS+
S3	TP-	S10	TS-
S4	Signal Ground	S11	Signal Ground
S5	RP-	S12	RS-
S6	RP+	S13	RS+
S7	Signal Ground	S14	Signal Ground

**NOTES:**

- Material:**  
 Housing: LCP+50%G.F, UL 94V-0 Rated.  
 Color: Black.  
 Contact: Phosphor Bronze.  
 Plating: Gold Plating over Nickel on Contact Area.  
 Tin Plating on Solder Tail.  
 Harpoon: Brass.  
 Plating: Tin Plating over Nickel.
- Mechanical:**  
 Insertion Force: 25N Max.  
 Withdrawal Force: 5N Min.  
 Durability: 500 Cycles
- Electrical Specification:**  
 Current Rating: 1.5 Ampere per Contact.  
 Contact Resistance: 30mΩ Max.  
 Insulation Resistance: 1000MΩ Min.  
 Dielectric Withstanding Voltage: 500 VAC.
- Environmental:**  
 Operating Temperature: 0°C to +55°C

RoHS Compliant		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 <b>Betty</b>		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM TOLERANCES ARE: DECIMALS ANGLES XX ± .25     ° ± 3° XXX ± .25     ° ± 20	PART NAME 品名 SAS CONNECTOR 29P(7+7+15) FEMALE DUAL ROWS STRAIGHT TYPE DIP LENGTH=2.6mm WITH BOARDLOCK BLACK COLOR(MATERIAL:LCP) ROHS
DWG. 製圖 <b>Betty</b>	SCALE 比例 參考	SIZE. 紙張尺寸 A 4	PART NO. <b>C7206-29FDSXBBR</b>
DATE 制表日 2013/07/11	PAGE 張數 1 OF 1	REV. 版次 A	料號

PCB LAYOUT(T=1.57mm)  
COMPONENT SIDE