



- SPECIFICATIONS:
- CONTACT CARRYING CAPACITY : AC : 100V 1A MAX.  
DC : 12V 2A MAX.
  - CONTACT RESISTANCE : 30 mΩ MAX.
  - INSULATION RESISTANCE : 50 MΩ MIN. AT DC 250V
  - VOLTAGE WITHSTAND : AC 250V FOR ONE MINUTE.
  - INSERTION FORCE : 1.0 - 4.5KG  
WITHDRAWAL FORCE : 0.8 - 3.0KG
  - OPERATING TEMP : -25°C TO +85°C

3.	EARTH TERMINAL	1	BSR-H 0.4t	Pb10%, Sn90%	
1.	BODY	1	P.B.T.	VALOX 420-SE0	UL94V-0
P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS

RoHS Compliant **HSM** 玄茂科技股份有限公司  
**HSUAN MAO TECHNOLOGY CO., LTD.**

ARRANGEMENT OF CONTACTS						
NO OF CONTACTS	3	4	5	6	7	8

APPD. 核准 HELEN	TOLERANCE 容許公差 .0 ± .00 ± .000 ±	PART NAME 品名 MINIATURE CIRCULAR CONNECTORS CRIMPING TYPE XXP QUICK LOCK TYPE TIN PLATED BLACK INSULATOR ROHS
DWG. 製圖 ABBY		
DATE 制表日 2015/07/07	SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1	REV. 版次 B PART NO. 料號 C8012-XXBTB000R