



NO.	NAME	MATERIAL	FINISH	Q'TY
1	HOUSING	PBT G.F.	BLACK	1
2	CONTACT	PHOS. BRONZE T:0.2	Gold:1~3u"; NI:40~60u"; TIN:120u" (100% pure Tin of lead free plating)	6
3	SHIELD	BRASS T:0.3	TIN PLATED Sn:120~200u"	1
4	BOTTOM COVER	PBT G.F.	BLACK	1
5	SPRING SHIELD	STAINLESS T:0.15		1

Specification:

Contact Resistance: 30m Ohm Max.
 Insulation Resistance: 100M Ohm Min. AT 500V DC
 Rated Voltage And Current: DC12V.2A Max; AC 100V.1A Max
 Dielectric Withstanding Voltage: 250V AC For 1 Minute
 Durability (Life Test): 100 Cycles
 Insertion Force: 4.0KG Maximum.
 Extraction Force: 0.9KG Minimum.
 Operating Temp: -25°C ~ +70°C

RoHS Compliant	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.		
	APPD. 核准 SCALE 比例 参考 UNIT 單位 MM DATE 制表日 2010/12/7	TOLERANCE 容許公差 .0 ± 0.25 .00 ± 0.13 ANG. ± SIZE 紙張尺寸 A4 REV. 版次 A	PART NAME 品名 MINI DIN JACK 6P FULLY SHIELDED+4 GND SPRING IN CORNER HOOK PIN TYPE SELECTIVE GOLD BLACK ROHS PART NO. 料號 C8102-06AHSB00R
	DWG. 製圖 HELEN		
	PAGE 張數 1 OF 1		