



Specification:

Contact Resistance: 30m Ohm Max.
 Insulation Resistance: 100M Ohm Min. AT 500V DC
 Rated Voltage And Current: DC12V, 2A Max; AC 100V, 1A Max
 Dielectric Withstanding Voltage: 250V AC For 1 Minute
 Durability (Life Test): 100 Cycles
 Insertion Force: 4.0KG Maximum.
 Extraction Force: 0.9KG Minimum.
 Operating Temp: -25°C~+70°C

NO.	NAME	MATERIAL	FINISH	Q'TY
1	HOUSING	PBT G.F.	BLACK	1
2	CONTACT	PHOS. BRONZE T:0.2	Gold(1~3u') NI:40~60u') TIN:120u' (100% pure Tin of lead free plating)	6
3	SHIELD	BRASS T:0.3	TIN PLATED Sn:120~200u'	1
4	BOTTOM COVER	PBT G.F.	BLACK	1
5	SPRING SHIELD	STAINLESS T:0.2		1

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 BETTY		TOLERANCE X ±0.38 X ±0.25 XX ±0.13 XXX ±0.05	PART NAME 品名 MINI DIN JACK 6P FULLY SHIELDED+GROUNDING STRIP HOOK PIN TYPE SELECTIVE GOLD BLACK INSULATOR ROHS
DWG. 製圖 KAREN	SCALE 比例 參考	UNIT 單位 MM	PART NO. 料號 C8102-06GHSB00R
DATE 制表日 2012/09/03	PAGE 張數 1 OF 1	SIZE 紙張尺寸 A4	REV. 版本 B