



NO.	NAME	MATERIAL	FINISH	QTY
1	EARTH TERMINAL	BRASS t=0.3	TIN PLATED	1
2	TIP SPRING	PHOSPHOR BRONZE t=0.3	TIN PLATED	1
3	RING SPRING	PBS t=0.3	TIN PLATED	1
4	COVER	PBT G.F.	BLACK	1
5	SPRING	STAINLESS STEEL	NICKEL PLATED	2
6	BUSHING	BRASS	NICKEL PLATED	1
7	HOUSING	PBT G.F.	BLACK	1

HOUSING & COVER COLOR	BLACK
PANTONE	-

Specification:

Contact Resistance: 30m Ohm. Max. At AC 100mA Max.1KHz.

Insulation Resistance: 100M Ohm Min. At 500V DC.

Rated Voltage And Current: DC 12V,2A Max ; AC 100V,1A Max.

Dielectric Withstanding Voltage: 500V AC For 1 Minute.

Durability (Life Test):

A: For Phosphor Bronze 1500 Cycles Minimum.

B: For PBS 2000 Cycles Minimum.

Insertion Force: 0.3-3.0 Kg.

Extraction Force: 0.3-3.0Kg.

RoHS
Compliant

HSM 宏茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPROVAL 核准 Karen		TOLERANCE 容許公差 X ± 0.30 Y ± 0.15 Z ± 0.25	PART NAME 品名 3.5Φ EARPHONE JACK 3P TIN PLATED BLACK INSULATOR ROHS LOW-LEAD
DWG. 製圖 Yumi		SCALE 比例 參考	PART NO. 料號 C8104-03NATB00R
DATE 制表日 2011/03/31	UNIT 單位 MM	SIZE 紙張尺寸 A 4	
	PAGE 張數 1 OF 1	REV. 版本 A	