



Specification:
 Contact Resistance: 30m Ohm. Max. At AC 100mA Max. 1KHz.
 Insulation Resistance: 100M Ohm Min. At 500V DC.
 Rated Voltage And Current: DC 12V, 2A Max ; AC 100V, 1A Max.
 Dielectric Withstanding Voltage: 500VAC At 60Hz For 1 Minute.
 Durability (Life Test): 4000 Cycles.
 Insertion Force: 0.3~3.0 Kg.
 Extraction Force: 0.3~3.0 Kg.

NO.	NAME	MATERIAL	FINISH	Q'TY
1	BARREL	BRASS T:0.4	NICKEL PLATED	1
2	INSERT RING	PBT G.F.	WHITE, RED	2
3	COVER	ABS	BLACK	1
4	HOUSING	ABS	WHITE	1
5	TOP TERM.	BRASS T:0.5	TIN PLATED	1
6	BOTTOM TERM.	BRASS T:0.5	TIN PLATED	1

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN		TOLERANCE 容許公差 X. ±0.38 .XX ±0.25 .XXX ±0.13 .XXXX ±0.05	PART NAME 品名 RCA JACK 2 PORT (WHITE/RED) VERTICAL TYPE RIGHT ANGLE O.D.=8.3mm (3P METAL FOOT, 2P PLASTIC FOOT) ROHS
DWG. 製圖 ABBY	SCALE 比例 參考	UNIT 單位 MM	SIZE. 紙張尺寸 A4
DATE 制表日 2015/09/23	PAGE 張數 1 OF 1	REV. 版次 B	PART NO. 料號 C8108-02VT0000R