



Specification:

Contact Resistance: 30m Ohm. Max. At AC 100mA Max.1KHz.
 Insulation Resistance: 100M Ohm Min. At 500V DC.
 Rated Voltage And Current: DC 12V,2A Max ; AC 100V,1A Max.
 Dielectric Withstanding Voltage: 500VAC At 60Hz For 1 Minute.
 Durability (Life Test): 4000 Cycles.
 Insertion Force: 0.3~3.0 Kg.
 Extraction Force: 0.3~3.0Kg.

NO.	NAME	MATERIAL	FINISH	Q'TY
1	BARREL	C.R.S T:0.30	TIN PLATED	1
2	RING	PBT G.F.	BLACK	1
3	INSULATOR	PBT G.F.	WHITE	1
4	BRACKET	C.R.S T:0.70	TIN PLATED	1
5	TERMINAL	BRASS T:0.25	TIN PLATED	1

RoHS Compliant	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
	APPD. 核准 DWG. 製圖 DATE 制表日 2013/06/17	SCALE 比例 UNIT 單位 M M PAGE 張數 1 / 1
PART NAME 品名 $\phi 3.5$ mm RCA JACK BLACK INSULATOR TIN PLATED ROHS		PART NO. 料號 C8109-02TB0000R