



RATING: DC30V 0.3A  
 WITHSTAND VOLTAGE: AC500V(50Hz)/min  
 CONTACT RESISTANCE:  $\leq 30m\Omega$   
 INSULATION RESISTANCE:  $\geq 100M\Omega$   
 WITHDRAW FORCE: 3-25N  
 LIFE TEST: 5,000 cycles  
 OPERATING TEMP:  $-20^{\circ}C \sim +70^{\circ}C$

6				
5				
4				
3				
2	TERMINAL	BRASS	3	Ag-Plating
1	HOUSING	PA66	1	BLACK
NO.	DESCRIPTION	MATERIAL	QTY.	PLATING

RoHS Compliant		<b>玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 <b>Betty</b>	 SCALE 比例 参考	TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3°	PART NAME 品名 φ2.5mm PHONE JACK SMT TYPE ALL PLASTIC WITH TWO LOCATING PEGS SILVER PLATING BLACK INSULATOR ROHS
DWG. 製圖 <b>Betty</b>	UNIT 單位 M M	SIZE 紙張尺寸 A 4	PART NO. 料號 C8113-03PAVB00R
DATE 制表日 2012/10/23	PAGE 張數 1 OF 1	REV. 版次 A	