



PCB LAYOUT
(BOTTOM VIEW)

Specification:

Contact Resistance: 30m Ohm Max. At AC 100mA Max.1KHz.

Insulation Resistance: 100M Ohm Min. At 500V DC.

Rated Voltage And Current: DC 12V,2A Max.

Dielectric Withstanding Voltage: 500VAC At 60Hz For 1 Minute.

Durability (Life Test): 4000 Cycles.

Insertion Force: 0.3~3.0 Kg.

Extraction Force: 0.3~3.0 Kg.

NO.	NAME	MATERIAL	FINISH	Q'TY
1	BARREL	C.R.S 0.30	NICKEL PLATED	1
2	RING	PBT	BLACK	1
3	INSULATOR	PBT	WHITE	1
4	BRACKET	C.R.S 0.40	NICKEL PLATED	1
5	TERMINAL	BRASS 0.25	TIN PLATED	1

RoHS Compliant **HSM 玄茂科技股份有限公司**
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准		TOLERANCE X. ±0.38 .X ±0.25 .XX ±0.13 .XXX ±0.05	PART NAME 品名 RCA JACK 3P(2 CONTACTS) STRAIGHT TYPE TIN PLATING BLACK INSULATOR ROHS
DWG. 製圖 Hedy		SCALE 比例 參考	SIZE. 紙張尺寸 A 4
DATE 制表日 2012/08/20	UNIT 單位 MM	REV. 版次 A	PART NO. 料號 C8127-03TB0000R
	PAGE 張數 1 / 1		