



SPECIFICATIONS:
 Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstanding Voltage: AC 500V for one minute
 Remark: ▲ : The Most Important Dimension

6.	Cover	PBT	1	Black Color
5.	Housing	PBT+30%G	1	Black Color
4.	Pin(1.3φ)	Copper	1	Nickel Plated
3.	Break Terminal	0.4T Brass	1	Silver Plated
2.	Sleeve Spring	0.2T Phosphor Bronze	1	Silver Plated
1.	Pin Terminal	0.4T Brass	1	Silver Plated
NO.	Description	Material	Q' TY	Finish

APPD. 核准 BETTY		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	PART NAME 品名 DC POWER JACK RIGHT ANGLE TYPE PINφ1.3mm NORMAL CLOSE SOLDER TAIL :FLAT TYPE SILVER PLATED BLACK INSULATOR ROHS
DWG. 製圖 BETTY	SCALE 比例 參考	TOLERANCE 容許公差 0 ±0.3 .00 ± ANG. ±	PART NO. 料號 C8132-ACFVB000R
DATE 制表日 2009/12/18	UNIT 單位 M M	SIZE. 紙張尺寸 A 4	
PAGE 張數 1 OF 1	REV. 版次 A		