



RATING: DC30V 0.5A
 WITHSTAND VOLTAGE: AC500V(50Hz)/min
 CONTACT RESISTANCE: 50mΩ max
 INSULATION RESISTANCE: 100MΩ min
 WITHDRAW FORCE: 3-30N
 LIFE TEST: 5,000 cycles

6				
5				
4	TERMINAL BASE	PHENOL RESIN	1	
3	HOUSING	PBT	1	BLACK
2	TERMINAL	BRASS	3	Ag-Plating
1	PIN	BRASS	1	Sn-Plating
NO.	DESCRIPTION	MATERIAL	QTY.	PLATING

APPD. 核准 Betty	 SCALE 比例 参考	TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3°	PART NAME 品名 DC POWER JACK PINφ2.0mm or φ2.5mm NORMAL CLOSE TYPE TIN PLATING BLACK INSULATOR ROHS
DWG. 製圖 Betty	DATE 制表日 2014/02/17	PAGE 張數 1 OF 1	REV. 版次 A
RoHS Compliant			HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD. PART NO. C8135-XCTB0000R 料號