



RATING: DC30V 0.5A
 WITHSTAND VOLTAGE: AC500V(50Hz)/min
 CONTACT RESISTANCE: $\leq 30m\Omega$
 INSULATION RESISTANCE: $\geq 100M\Omega$
 WITHDRAW FORCE: 3-20N
 LIFE TEST: 5,000 cycles

NO.	DESCRIPTION	MATERIAL	QTY.	PLATING
3	PIN	BRASS	1	Ni -Plating
2	TERMINAL	BRASS	3	Ag -Plating
1	HOUSING	PBT	1	BLACK

APPD. 核准 HELEN		SCALE 比例 参考		TOLERANCE 容許公差 0 ± .00 ± ANG. ±		PART NAME 品名 DC POWER JACK RIGHT ANGLE TYPE PINφ0.7mm NORMAL CLOSE TYPE WITH LOCATING PEG WITHOUT SHIELDED SILVER PLATING BLACK COLOR	
DWG. 製圖 ABBY		UNIT 單位 MM		SIZE. 紙張尺寸 A4		PART NO. 料號 C8136-GCVBN000R	
DATE 制表日 2014/12/30		PAGE 張數 1 OF 1		REV. 版次 A			

RoHS Compliant **HSM** 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.