



T:1.6 Dimensions of PC board holes
Tolerance : ±0.1(Printed-top view)

LEAD FREE

CAT. NO.	PIN	SCHEMATIC
C8318-ECVBY000R	φ1.0	
C8318-ACVBY000R	φ1.3	

5	HOUSING	1	PBT 4815	UL-94V0(BLACK)
4	PIN	1	C2680	MB:Cu Ni PLATED
3	SHUNT TERMINAL	1	C2680 t=0.3	MB:Cu Ag PLATED
2	TIP SPIRING	1	SUS 301 t=0.3	MB:Cu Ag PLATED
1	CENTER PIN TERMINAL	1	C2680 t=0.3	MB:Cu Ag PLATED
LTR	PART NAME	QTY	MATERIAL	REMARK

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

RoHS Compliant **HSM** 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准 Betty		TOLERANCE 容許公差 0 ± .00 ± ANG. ±	PART NAME 品名 DC POWER JACK RIGHT ANGLE TYPE PINφ1.0mm or φ1.3mm NORMAL CLOSE TYPE SILVER PLATING BLACK INSULATOR WITH LOCATING PEG
DWG. 製圖 Yumi	SCALE 比例 參考	SIZE. 紙張尺寸 A 4	PART NO. 料號 C8138-XCVBY000R
DATE 制表日 2010/01/06	UNIT 單位 M M	REV. 版次 A	
	PAGE 張數 1 OF 1		