



10.	Washer	0.3T Steel	1	Nickel Plated
9.	Nut	2.0T Steel	1	Nickel Plated
8.	Insulator B	Red Vulcanited Fibre	1	Red Color
7.	Insulator A	Red Vulcanited Fibre	1	Red Color
6.	Pin(2.0φ)	Low Lead Brass Rod	1	Nickel Plated
5.	Bushing	Low Lead Brass Rod	1	Nickel Plated
4.	Pin Terminal	0.3T Brass	1	Silver Plated
3.	Break Terminal	0.3T Brass	1	Silver Plated
2.	Sleeve Spring	0.4T Phosphor Bronze	1	Silver Plated
1.	Housing	PBT+15%	1	Black Color
NO.	Description	Material	Q'TY	Finish

SPECIFICATIONS:
 Contact Resistance : 30mΩ max
 Current Rating : Max 5.0A , 24V DC
 Insulation Resistance: 100MΩ min. at DC 500V
 Dielectric Withstanding Voltage: AC 500V for one minute
 Remark: ▲ : The Most Important Dimension

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty		TOLERANCE 容許公差 0 ± 0.30 .00 ± 0.30 ANG. ± 3°	PART NAME 品名 DC POWER JACK RIGHT ANGLE TYPE PINφ2.0mm NORMAL CLOSE TYPE FLAT TYPE WITH THREAD SILVER PLATING BLACK INSULATOR WITH NUT & WITH WASHER ROHS
DWG. 製圖 Lena	SCALE 比例 參考	UNIT 單位 MM	PART NO. C8141-CCFYVBY0R
DATE 制表日 2023/6/19	PAGE 張數 1 OF 1	REV. 版本 C	料號 C8141-CCFYVBY0R

