



Specification:
 Current Rating: 5A
 Voltage Rating: 750V max
 Operating Temp: -30°C~+60°C
 Insulation Resistance: ≤100MΩ
 Dielectric Withstanding Voltage: 2000V rms
 Contact Resistance: ≤20mΩ

7	CRIMPING PATCH	Fe
6	SOLDERING PATCH	BRASS
5	DIELECTRIC	POM
4	BODY	BRASS
3	SHELL	ABS
2	DIELECTRIC	POM
1	FRONT POINT	BRASS
ITEM	DESIGNATION	MATERIAL

TOLERANCE	
0 - 10	±0.05
10 - 99	±0.5
100 - 999	±10.0
1000 - 9999	±100.00
10000 - 99999	±1000.00

APPD. 核准 DWG. 製圖 DATE 制表日 2016/5/12	Helen	TOLERANCE 零件公差 0 ± 0.35 .00 ± 0.25 ANG. ± 3°	PART NAME 品名 3.5mm PHONE PLUG STERO PLASTIC ROUND TYPE(ABS) NICKEL PLATING BLACK COLOR ROHS
SCALE 比例 參考	UNIT 單位 MM	SIZE 紙張尺寸 A4	PART NO. 料號 C8150-03MBBNB0R
PAGE 張數 1 OF 1	REV. 版本 B		