



NO OF POS.	DIM. A	DIM. B
1	2.44[.096]	
2	4.88[.196]	2.54[.100]
3	7.52[.296]	5.08[.200]
4	10.08[.396]	7.62[.300]
5	12.80[.496]	10.16[.400]
6	15.14[.596]	12.70[.500]
7	17.88[.696]	15.24[.600]
8	20.22[.796]	17.78[.700]
9	22.76[.896]	20.32[.800]
10	25.30[.996]	22.86[.900]
12	30.38[1.196]	27.94[1.100]



NOTE:  
 1. ALL DIMENSIONS ARE IN MILLIMETERS, BRACKETED DIMENSIONS ARE IN INCHES.  
 2. GENERAL TOLERANCES MAX ±0.20mm.

ITEM	DESC.	Q'TY	MATERIALS	TREATMENT	REMARK
1.	COVER	1	HIGH - TEMP THERMOPLASTIC PA-9T UL 94V-0	MOLDED BLACK	-
2.	CONTACT	*	COPPER	GOLD PLATED AT CONTACT AREA	-
3.	ACTUATOR	*	THERMOPLASTIC LCP UL 94V-0	MOLDED WHITE	-
4.	TERMINAL	1	BRASS	GOLD PLATED	-
5.	BASE	1	HIGH - TEMP THERMOPLASTIC PA9T UL 94V-0	MOLDED BLACK	-
-	-	-	-	-	-

RoHS Compliant

**HSM** 玄茂科技股份有限公司  
 HSUAN MAO TECHNOLOGY CO., LTD.

APPR. 核准: <b>BETTY</b> DWG. 数据: <b>BETTY</b>		TOLERANCE 容许公差: 0 ± .00 ± ANG. ±	PART NAME 品名: DIP SWITCH IC TYPE XXP H 2.8MM SPLAY TERMINAL GOLD 3U' ROHS LOW-LEAD
DATE 列表日: 2008/08/01	UNIT 单位: M M PAGE 页数: 1 OF 1	SIZE 规格尺寸: A 4 REV. 版本: A	PART NO. 料号: C8309-XXAXXJB0R