



H= (A)4.3 , (B)5.0 , (C)7.0 , (D)8.0 , (E)9.5mm

RATING: DC12V 50mA  
 WITHSTAND VOLTAGE: AC250V(50Hz)/min  
 CONTACT RESISTANCE: 100mΩ max  
 INSULATION RESISTANCE: 100MΩ min  
 TRAVEL TO CLOSURE: 0.25±0.1mm  
 OPERATION FORCE: 160gf±50gf 250gf±50gf  
 LIFE TEST: 100,000 cycles

NO.	DESCRIPTION	MATERIAL	QTY.	PLATED
6				
5	TERMINAL	BRASS	4	Ag-PLATED
4	SPRING	PHOSPHOR BRONZE	1	
3	HOUSING	PA66	1	BLACK
2	COVER	SPCC	1	Ni-PLATED
1	KNOB	PA66	1	BLACK

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 DWG. 製圖 DATE 制表日 2017/05/26	SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 / 1	TOLERANCE X±0.1 XX±0.05 SIZE. 紙張尺寸 A 4 REV. 版次 A	PART NAME 品名 TACT SWITCH SMT TYPE PORD. SIZE: 6X6mm KONB HEIGHT : XXmm PITCH: XXmm OPERATING FORCE: XXXg BLACK COLOR BAG PACKING ROHS PART NO. 料號 C8310-XXXBB000R