



KNOB HEIGHT:  
 A:4.3mm  
 B:5.0mm  
 C:7.0mm  
 L:7.5mm  
 D:8.0mm  
 S:9.0mm  
 E:9.5mm  
 M:10.0mm  
 N:12.0mm  
 J:13.0mm

RATING: DC12V 50mA  
 WITHSTAND VOLTAGE: AC250V(50Hz)/min  
 CONTACT RESISTANCE:  $\leq 30m\Omega$   
 INSULATION RESISTANCE:  $\geq 100M\Omega$   
 TRAVEL TO CLOSURE:  $0.25\pm 0.1mm$   
 OPERATION FORCE:  $160gf\pm 50gf$   
 LIFE TEST: 100,000 cycles

NO.	DESCRIPTION	MATERIAL	QTY.	PLATED
6				
5	HOUSING	PA66	1	BLACK
4	CONTACT	PBS	1	
3	COVER	SPCC	1	Ni-PLATED
2	TERMINAL	BRASS	4	Ag-PLATED
1	KNOB	PA66	1	BLACK

APPD. 核准 Betty	SCALE 比例 参考	TOLERANCE 容許公差	PART NAME 品名
		.0 ± 0.30 .00 ± 0.20 ANG. ± 3°	
DWG. 製圖 Betty	UNIT 單位 MM	SIZE 紙張尺寸 A 4	PART NO. 料號 C8316-XBNBB000R
DATE 制表日 2016/09/26	PAGE 張數 1 OF 1	REV. 版次 B	

RoHS Compliant **HSM** 玄茂科技股份有限公司  
**HSUAN MAO TECHNOLOGY CO., LTD.**