



NOTES:

1.MATERIAL:

- 1.1 Housing:PBT ,UL94-HB
- 1.2 terminals:Copper Alloy  
Gold plated in contact area:  
Tin 40u"min plated in termination  
Nickel Plated overall
- 1.3 Shell:SPCC t=0.30mm,  
Nickel 40u"min Plated overall

2.ELECTRICAL CHARACTERISTICS:

- 2.1 Rating Current :1.5 Ampere
- 2.2 Rating Voltage :30 V Max
- 2.3 Contact Resistance:30 Milli ohms
- 2.4 Insulation Resistance:1000 Mega ohms Min.

3.MECHANICAL CHARACTERISTICS:

- 3.1 Connector Mating force: 35N MAX(3.57Kgf)
- 3.2 Connector Unmating force:10N min(1.02Kgf)
- 3.3 Durability:1500Cycles.

4.ENVIRONMENT CHARACTERISTICS:

- 4.1 Operating temperature:-0°C to +50°C
- 4.2 Storage temperature:-20°C to +60°C

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准		<b>TOLERANCE</b> 容許公差	<b>PART NAME</b> 品名
DWG. 製圖	<i>Helen</i>	0 ± 0.35 .00 ± 0.25 ANG. ± 3°	USB B TYPE DIP TYPE 4P FEMALE STRAIGHT TYPE NICKEL SHELL ROHS
DATE 制表日	UNIT 單位	SIZE. 紙張尺寸	<b>PART NO.</b>
2020/12/1	M M	A 4	C8317-04BFSXX0R
	PAGE 張數	REV. 版本	料號
	1 OF 1	B	