


Specification:
 Contact Resistance: 30m Ohm Max.
 Insulation Resistance: 1000M Ohm Min. At 500VDC.
 Rated Voltage And Current: 1.5A At 250VAC Minimum.
 Dielectric Withstanding Voltage: 750V AC (rms) for 1 Minute (Rev. 1.1)
 Durability (Life Test): 1500 Cycles
 Insertion Force: 35 Newton Maximum.
 Extraction Force: 10 Newton Minimum.

Green Product



NO.	NAME	MATERIAL	FINISH	Q'TY	REMARK
1	HOUSING	PBT G.F.	WHITE	1	
2	PIN TERM.	PHOS. BRONZE T:0.25	GOLD-TIN PLATED	16	Gold:1~3u"; Ni:40~60u"; TIN:21u" (100% pure Tin of lead free plating)
3	SHELL	BRASS, T:0.4	TIN PLATED	1	TIN:120~200u"
4	SPRING CLIP	BRASS, T:0.3	TIN PLATED	3	TIN:120~200u"
5	REAR SHELL	SPCC, T:0.3	NICKEL PLATED	1	NI:80~120u"
6	BOTTOM COVER	PBT G.F.	WHITE	1	

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 DWG. 製圖 Hedy DATE 制表日 2012/06/27	SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 / 1	TOLERANCE 容許公差 X. ±0.38 XX. ±0.25 XXX. ±0.13 XXXX ±0.05	PART NAME 品名 USB A TYPE FEMALE FOUR PORT 4X4P R/A TYPE 90° HORIZONTAL SELECTIVE GOLD PLATING WHITE COLOR ROHS PART NO. 料號 C8317-16EFHSW0R