



Specification:

Contact Resistance: 30m Ohm Max.

Insulation Resistance: 100M Ohm Min.

Voltage - Max: 40V Maximum

Current - Max: 1.5A Maximum.

Dielectric Withstanding Voltage:

500V AC for 1 Minute

Durability (Life Test): 1500 Cycles

Unmating Force: 9.8 Newton TO 39.2 Newton Maximum.

NO.	NAME	MATERIAL	FINISH	REMARK	Q'TY
1	HOUSING	NYLON PA9T G.F.	BLACK		1
2	PIN TERMINAL	BRASS; ±0.25	GOLD/TIN PLATED	Gold:30u" NI:40~60 u" TIN:120u" (100% pure Tin of lead free plating)	6
3	SHELL	BRASS; ±0.4	NICKEL PLATED	NI:80~120u"	1

RoHS Compliant	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.							
	APPD. 核准 DWG. 製圖 DATE 制表日 2012/08/03	Hedy 2012/08/03	<table border="1"> <tr> <td> TOLERANCE 容許公差 X, ±0.38 Y, ±0.25 XX, ±0.13 XXX, ±0.05 </td> <td> PART NAME 品名 IEEE 1394 CONNECTOR 6P FEMALE SMT TWO METAL POSTS & TWO PLASTIC POSTS NICKEL SHELL SELECTIVE GOLD 30U" PLATING BLACK COLOR ROHS </td> </tr> <tr> <td> SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 / 1 </td> <td> SIZE. 紙張尺寸 A 4 REV. 版次 A </td> </tr> <tr> <td colspan="2"> PART NO. 料號 C8318-06FDAIB0R </td> </tr> </table>	TOLERANCE 容許公差 X, ±0.38 Y, ±0.25 XX, ±0.13 XXX, ±0.05	PART NAME 品名 IEEE 1394 CONNECTOR 6P FEMALE SMT TWO METAL POSTS & TWO PLASTIC POSTS NICKEL SHELL SELECTIVE GOLD 30U" PLATING BLACK COLOR ROHS	SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 / 1	SIZE. 紙張尺寸 A 4 REV. 版次 A	PART NO. 料號 C8318-06FDAIB0R
TOLERANCE 容許公差 X, ±0.38 Y, ±0.25 XX, ±0.13 XXX, ±0.05	PART NAME 品名 IEEE 1394 CONNECTOR 6P FEMALE SMT TWO METAL POSTS & TWO PLASTIC POSTS NICKEL SHELL SELECTIVE GOLD 30U" PLATING BLACK COLOR ROHS							
SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 / 1	SIZE. 紙張尺寸 A 4 REV. 版次 A							
PART NO. 料號 C8318-06FDAIB0R								