



**Specification:**  
**Contact Resistance: 30m Ohm Max.**  
**Insulation Resistance: 100M Ohm Min.**  
**Voltage - Max:40V Maximum**  
**Current - Max:1.5A Maximum.**  
**Dielectric Withstanding Voltage: 500V AC for 1 Minute.**  
**Durability (Life Test): 1500 Cycles**  
**Unmating Force:9.8 Newton TO 39.2 Newton Maximum.**

NO.	NAME	MATERIAL	FINISH	REMARK	Q'TY
1	HOUSING	PBT G.F.	BLACK		1
2	PIN TERMINAL	BRASS; t±0.25	GOLD/TIN PLATED	Gold:30u* Ni:40~60u* TIN:120u* (100% pure Tin of lead free plating)	6
3	SHELL	BRASS; t±0.4	NICKEL PLATED	Ni:80~120u*	1
4	BOTTOM COVER	PBT G.F.	BLACK		1

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Hedy	SCALE 比例 參考	TOLERANCE 容許公差 X ±0.38 .X ±0.25 .XX ±0.13 .XXX ±0.05	PART NAME 品名 IEEE 1394 6P FEMALE 180° TWO METAL POSTS BLACK COLOR NICKEL SHELL ROHS LOW-LEAD
DWG. 製圖 Yumi	UNIT 單位 MM	SIZE 紙張尺寸 A 4	PART NO. 料號 C8318-06FSBXB0R
DATE 制表日 2010/11/24	PAGE 張數 1 OF 1	REV. 版次 A	