



Specification:
 Contact Resistance: 30m Ohm Max.
 Insulation Resistance: 100M Ohm Min.
 Voltage - Max; 40V Maximum.
 Current - Max: 1.5A Maximum.
 Dielectric Withstanding Voltage: 500V AC for 1 Minute
 Durability (Life Test): 1500 Cycles
 Unmating Force: 9.8 Newton TO 39.2 Newton Maximum.

NO.	NAME	MATERIAL	FINISH	REMARK	Q'TY
1	HOUSING	PBT G.F.	BLACK		1
2	PIN TERMINAL	BRASS; ±0.25	GOLD/TIN PLATED	Gold: 30u" Ni: 40~60 u" TIN: 120u" (100% pure Tin of lead free plating)	6
3	SHELL	BRASS; ±0.4	NICKEL PLATED	Ni: 80~120u"	1
4	BOTTOM COVER	PBT G.F.	BLACK		1

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Angel	SCALE 比例 参考	TOLERANCE X +0.30 XX +0.25 XXX +0.150 Ang ±2°	PART NAME 品名 IEEE 1394 6P FEMALE 90° VERTICAL THREE METRAL POSTS NICKEL SHELL ROHS
DWG. 製圖 Yumi			
DATE 製表日 2010/06/09	PAGE 張數 1 OF 1	REV. 版次 A	PART NO. 料號 C8318-06FVCXX0R