



Specifications:

Electrical:

1. Current Rating  
1.5A/contact terminal
2. Voltage Rating  
30V DC
3. Contact Resistance  
30 milliohms MAX
4. Dielectric Withstanding Voltage:  
500 V AC AT Sea Level
5. Insulation Resistance:  
1000MEGA ohms MIN

Mechanical:

1. Connector Mate and Unmate Force  
Mate force: 3.75kgf (MAX)  
Unmate force: 1.02kgf (MIN)
2. Terminal Retention  
1.2kgf (MIN)

Material:

1. Housing:  
Hing Temperature Tnermaplastics,  
Ul 94V-0 PBT White/Black
2. Contact: Copper Alloy C2680
3. Shell: Copper Alloy C2680/SPCC

Finish:

1. Contact: Plated Gold in Mating Area;  
Tin On Solder Talls
2. Shell:  
Nickel Plating

<p>RoHS Compliant</p>		<p><b>HSM</b> 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.</p>	
<p>APPD. 核准 BETTY</p>	<p>SCALE 比例 参考</p>	<p>TOLERANCE X.X ±0.30 X.XX ±0.20 X.XXX ±0.10 X° ±5° X.X° ±2°</p>	<p>PART NAME 品名 USB A TYPE DIP TYPE SHORT BODY 4P FEMALE RIGHT ANGLE VERTICAL TYPE NICKEL SHELL ROHS</p>
<p>DWG. 製圖 KAREN</p>	<p>UNIT 單位 MM</p>	<p>SIZE 紙張尺寸 A4</p>	<p>PART NO. 料號 C8323-04AFVXX0R</p>
<p>DATE 制表日 2015/05/04</p>	<p>PAGE 張數 1 OF 1</p>	<p>REV. 版本 B</p>	