



NOTES:

1. MATERIAL SPECIFICATION:

- 1) INSULATION MATERIAL: THERMOPLASTIC (UL94V-0)
- 2) SHELL: SD-SPCC COVER: COPPER ALLOY  
PLATING: NICKEL OR TIN PLATED;
- 3) TERMINAL: COPPER ALLOY  
PLATING: GOLD/TIN PLATED;

2. ELECTRICAL CHARACTERISTIC:

- 1) VOLTAGE CURRENT RATING: 1AMP, 30V DC;
- 2) INSULATION RESISTANCE: 100MΩ MIN;
- 3) CONTACT RESISTANCE: 50mΩ MAX;
- 4) WITHSTANDING VOLTAGE: 100V AC;

RoHS Compliant		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 HELEN	SCALE 比例 參考	TOLERANCE X. ±0.15 X*. ±2* .XX ±0.10 .XX* ±2* .XXX ±0.02 .XXX* ±0.5*	PART NAME 品名 IEEE 1394 SOLDER TYPE 4P MALE STRAIGHT BLACK INSULATOR ROHS
DWG. 製圖 ABBY		UNIT 單位 MM	SIZE. 紙張尺寸 A 4
DATE 制表日 2015/03/23	PAGE 張數 1 OF 1	REV. 版次 A	PART NO. 料號 C8324-04MSXB00R