



NO.	DESCRIPTION	MATERIAL	COLOR	REMARK
4	TERMINAL	C5191	—	GOLD/TIN PLATED
3	HOUSING	PBT	BLACK/WHITE	UL 94V-0
2	UPPER COVER	SPCC-SD	—	NICKEL /GOLD PLATED
1	BOTTOM COVER	SPCC-SD	—	NICKEL /GOLD PLATED

Specifications:

1. Current Rating: 1.5A at 40V AC.
2. Withstanding Voltage: 500V AC for one minute.
3. Insulation Resistance: 100MΩ Min.
4. Contact Resistance: 30mΩ Max.
5. Mating Force: 4.0kgf Max.
6. Unmating Force: 1.0kgf Min.

<p>RoHS Compliant</p>		<p>HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.</p>	
<p>APPD. 核准 HELEN</p>	<p>SCALE 比例 参考</p>	<p>TOLERANCE X. ±0.30 X.X ±0.20 X.XX ±0.15 Angle ±2°</p>	<p>PART NAME 品名 IEEE 1394 SOLDER TYPE 6P MALE BLACK INSULATOR ROHS</p>
<p>DWG. 製圖 ABBY</p>	<p>UNIT 單位 MM</p>	<p>SIZE 紙張尺寸 A 4</p>	<p>PART NO. 料號 C8324-06MSXB00R</p>
<p>DATE 制表日 2017/03/08</p>	<p>PAGE 張數 1 OF 1</p>	<p>REV. 版次 A</p>	