



Specification:

Contact Resistance: 30m Ohm Max.

Insulation Resistance: 1000M Ohm Min. At 500VDC.

Rated Voltage And Current: 1.5A At 250VAC Minimum.

Dielectric Withstanding Voltage: 750V AC (rms) for 1 Minute (Rev. 1.1).

Durability (Life Test): 1500 Cycles.

Insertion Force: 35 Newton Maximum.

Extraction Force: 10 Newton Minimum.

NO.	NAME	MATERIAL	FINISH	Q'TY	REMARK
1	HOUSING	NYLON PA9T G.F.	BLACK	1	
2	TERMINAL	PHOS. BRONZE T:0.25	GOLD/TIN PLATED	4	Gold(1~3u'), Ni(40~60u'), TIN(120u') (100% pure Tin of lead free plating)
3	SHELL	BRASS T:0.3	NICKEL PLATED	1	Ni(80~120u')

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		TOLERANCE X. ±0.38 .X ±0.25 .XX ±0.13 .XXX ±0.05	PART NAME 品名 USB A TYPE 4P FEMALE SMT TYPE SHELL DIP L=2.3mm SMT PIN L=2.4mm NICKEL SHELL SELECTIVE GOLD PLATING BLACK COLOR(NYLON 9T) TRAY PACKING ROHS
DWG. 製圖 Betty	SCALE 比例 參考	UNIT 單位 MM	PART NO. 料號 C8332-04AFDCSB0B
DATE 制表日 2014/08/15	PAGE 張數 1 OF 1	SIZE. 紙張尺寸 A 4	REV. 版次 A