



Specifications:

Electrical:

1. Current Rating
1.5A/contact terminal
2. Voltage Rating
30V DC
3. Contact Resistance
30 milliohms MAX
4. Dielectric Withstanding Voitage:
500 V AC AT Sea Level
5. Insulation Resistance:
1000MEGA ohms MIN

Mechanical:

1. Connector Mate and Unmate Force
Mate force:3.57kgf (MAX)
Unmate force:1.02kgf (MIN)
2. Terminal Retention
1.2kgf (MIN)

Material:

1. Housing:
PBT WHITE/BLACK
2. Shell:SPCC
Nickel Plating
2. Contact:Copper Alloy C2680

Finish:

1. Contact: Plated Gold in Mating Area;
Tin On Solder Talls

RoHS Compliant		HSM 玄茂科技股份有限公司		HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例 参考	TOLERANCE .X ±0.30 .XX ±0.20 .XXX ±0.10 ANGLES ±2.00°	PART NAME 品名		
DWG. 製圖		UNIT 單位	SIZE. 紙張尺寸	USB A TYPE DUAL PORTS 8P FEMALE 180° DIP TYPE SHORT BODY NICKEL SHELL SELECTIVE GOLD PLATING ROHS	
DATE 制表日	PAGE 張數	REV. 版次	PART NO.		
2024/01/12	1 / 1	D	料號 C8339-08CFSSX0R		