



**SPECIFICATIONS:**

Contact current Rating:

1.8 Amperes for pin1&pin4.

0.25 Amperes other contacts

Dielectric Withstanding Voltage:AC 100V(RMS)

Insulation resistance:100Megohms Minimum.

Contact Resistance:

30m Ω Max for pin1&pin4

50m Ω Max for other contacts

Mechanical Characteristics:

Mating Force:35 Newtons.Maximum

Unmating Force:10 Newtons.Mlimum.

MATERIAL: 8N Min After Durability

Housing: PBT+30%GF 94V-0 COLOR:BLUE

Contact: copper alloy ( T=0.25mm)

Shell: Brass

PLATING:

Contact: Au Plated on contact area

Tin Plated on solder area

Nickel underplating over all

Shell: Nickel Plated

operating Temperature:-55° to+85°

<p>RoHS Compliant</p>		<p><b>HSM</b> 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.</p>	
<p>APPD. 核准</p>	<p>SCALE 比例 参考</p>	<p>TOLERANCE 容許公差 0 ± 0.35 .00 ± 0.25 ANG. ± 3°</p>	<p>PART NAME 品名 USB A TYPE 3.0VER. DIP TYPE 9P FEMALE STRAIGHT TYPE SELECTIVE GOLD PLATING MATERIAL:PBT BLUE COLOR ROHS</p>
<p>DWG. 製圖 Helen</p>	<p>UNIT 單位 MM</p>	<p>SIZE 紙張尺寸 A4</p>	<p>PART NO. 料號 C8341-09AFSPXLR</p>
<p>DATE 制表日 2016/5/3</p>	<p>PAGE 張數 1 OF 1</p>	<p>REV. 版本 B</p>	