



MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0),
 SHELL: COPPER ALLOY, NICKEL PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
 TIN PLATING ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 1.5A MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -40°C~85°C

PIN NUMBER	SIGNAL NAME	PIN NUMBER	SIGNAL NAME
1	VBUS	6	StdA_SSRX+
2	D-	7	GND_DRAIN
3	D+	8	StdA_SSTX-
4	GND	9	StdA_SSTX+
5	StdA_SSRX-	Shell	Shield

RECOMMENDED P.C.B LAYOUT(1.0~1.60±0.05)

<p>RoHS Compliant</p>		<p>HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.</p>	
<p>APPD. 核准 HELEN</p>	<p>SCALE 比例 參考</p>	<p>TOLERANCE 容許公差 .0 ±0.30 .00 ±0.20 .000 ±0.10</p>	<p>PART NAME 品名 USB 3.0 VERSION A TYPE 9P FEMALE OFF-SET TYPE SMT TYPE MATERIAL:LCP BLUE COLOR TRAY PACKING ROHS</p>
<p>DWG. 製圖 ABBY</p>	<p>UNIT 單位 MM</p>	<p>SIZE. 紙張尺寸 A 4</p>	<p>PART NO. 料號 C8346-09AFDLXLR</p>
<p>DATE 制表日 2017/12/25</p>	<p>PAGE 張數 1 OF 1</p>	<p>REV. 版次 A</p>	