



Specifications:

Electrical:

1. Current Rating:1.0A/Contact Termina.
2. Voltage Rating:30V DC.
3. Contact Reslstance:50 milliohms MAX.
4. Dielectnic Withstanding Voltage: 300V AC AT Sea Level.
5. Lnsulation Resistance:100MEGA ohms Min

Mechanical:

1. Connector Mate and Unmate Force
Mate Force:3.0kgf(MAX)
Unmate force:0.7kgf(MIN)
2. Terminal Retention:0.5kgf(MIN)

Material:

1. Housing:High Temperature Thermoplastics. UL94V-0 LCP Black..
2. Terminal:Alloy C2680.
3. Shell:SUS 304.

Finish:

1. Contact:Plated Gold XXu in Mating Area ;Tin On Solder Tails.
2. Shell:Nickel Plating.

<p>RoHS Compliant</p>		<p>HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.</p>	
<p>APPD. 核准</p>		<p>TOLERANCE 容許公差</p> <p>.0 ± 0.30</p> <p>.00 ± 0.20</p> <p>ANG. ± 3°</p>	<p>PART NAME 品名</p> <p>Micro USB B TYPE FEMALE 5P PIN FOOT:SMT TYPE</p>
<p>DWG. 製圖</p> <p>Betty</p>	<p>SCALE 比例 參考</p>	<p>SIZE. 紙張尺寸</p> <p>A 4</p>	<p>SHELL FOOT:DIP TYPE WITHOUT LOCATING PEG</p> <p>NICKEL SHELL</p> <p>BLACK INSULATOR MATERIAL:LCP ROHS</p>
<p>DATE 制表日</p> <p>2018/04/20</p>	<p>PAGE 張數</p> <p>1 OF 1</p>	<p>REV. 版次</p> <p>A</p>	<p>PART NO. 料號</p> <p>C8368-05BFBXNNXR</p>