



NOTE:

1. ELECTRICAL CHARACTERISTICS
 - 1-1. VOLTAGE RATING:30V AC
 - 1-2. CURRENT RATING:1.0A
 - 1-3. CONTACT RESISTANCE: 50 milliohms MAX.
 - 1-4. INSULATION RESISTANCE: 100 Megohms MIN.
 - 1-5. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE.
2. MECHANICAL CHARACTERISTICS
 - 2-1. RETENTION FORCE:MIN.300gf/PIN
 - 2-2. DURABILITY:5000CYCLES
3. OPERATING TEMPERATURE:-55°C~85°C
4. RoHS 2002/95/EC COMPLIANT.

| | | | | | |
|------|----------|------|---------------|------------|--|
| 3 | TERMINAL | 10 | COPPER ALLOY | Au PLATING | CONTACT AREA:GOLD PLATING,TIN PLATING ON SOLDER-TAIL |
| 2 | SHIELD | 1 | COPPER ALLOY | Ni PLATING | ————— |
| 1 | HOUSING | 1 | THERMOPLASTIC | ————— | UL 94V-0,COLOR:BLACK |
| ITEM | NAME | Q'TY | MATERIAL | FINISHED | NOTE |

| | | |
|------------------------|--|---|
| RoHS Compliant | HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD. | |
| | APPD. 核准 | TOLERANCE X ±0.25 X.X ±0.20 X.XX ±0.15 X.XXX ±0.10 X' ±2.0° X.X' ±1.0° |
| DWG. 製圖 Betty | SCALE 比例 參考 | PART NAME 品名 Mini USB B Type 10Pin Male Splint Type Without P.C.B. Selective Gold Plating Black Color ROHS |
| DATE 制表日 2018/06/15 | UNIT 單位 M M PAGE 張數 1 OF 1 | PART NO. 料號 C8388-10BMNSB0R |