



NOTE:

1. ELECTRICAL CHARACTERISTICS
 - 1-1. VOLTAGE RATING:30V AC
 - 1-2. CURRENT RATING:1.0A
 - 1-3. CONTACT RESISTANCE: 50 milliohms MAX.
 - 1-4. INSULATION RESISTANCE: 100 Megohms MIN.
 - 1-5. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE.
2. MECHANICAL CHARACTERISTICS
 - 2-1. RETENTION FORCE:MIN.300gf/PIN
 - 2-2. **DURABILITY:5000CYCLES**
3. SALT SPRAY: 12H
4. OPERATING TEMPERATURE:-55°C~85°C
5. RoHS 2002/95/EC COMPLIANT.
6. CRITICAL DIMENSIONS : ▼

4	PCB	1	FR4	—————	
3	TERMINAL	10	C5191	Au PLATING	Au: G/F ; TIN PLATING ON SOLDER-TAIL
2	SHIELD	1	SPCC	Ni PLATING	NI PLATED ALL OVER
1	HOUSING	1	LCP	—————	UL 94V-0,COLOR:BLACK
ITEM	NAME	Q'TY	MATERIAL	FINISHED	NOTE

RoHS Compliant **HSM** 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准		TOLERANCE	PART NAME 品名											
DWG. 製圖		<table border="1"> <tr><td>X</td><td>±0.25</td></tr> <tr><td>X.X</td><td>±0.20</td></tr> <tr><td>X.XX</td><td>±0.15</td></tr> <tr><td>X.XXX</td><td>±0.10</td></tr> <tr><td>X.XX</td><td>±2.0°</td></tr> <tr><td>X.X°</td><td>±1.0°</td></tr> </table>	X	±0.25	X.X	±0.20	X.XX	±0.15	X.XXX	±0.10	X.XX	±2.0°	X.X°	±1.0°
X	±0.25													
X.X	±0.20													
X.XX	±0.15													
X.XXX	±0.10													
X.XX	±2.0°													
X.X°	±1.0°													
DATE 制表日	UNIT 單位	SCALE 比例	PART NO.											
2018/06/15	M M	參考	料號 C8388-10BMYSB0R											
	PAGE 張數	REV. 版次												
	1 OF 1	A												