



- Specification:
1. Current Rating: 1.0 AMP
 2. Voltage Rating: 30V AC,DC
 3. Dielectric Strength: 500V AC RMS for 1 minute.
 4. Contact Resistance: 30 mΩ Max.
 5. Insulator Resistance: 500M Ω Min. AT 250V DC.
 6. Mating/Unmating cycles: 2000cycles
 7. Temperature: -20°C to +60°C

WATER PROOFNESS: THIS PRODUCT IS BASED ON IP66

ITEM	PART NAME	Q'TY	FINISH
4	O-Ring	1	Black rubber
3	Shell	1	C2680R-H Au/Ni Plating T=0.30mm
2	Contact	5	Phosphor bronze Au1u' /Over Ni50u' Plating T=0.20mm
1	Housing	1	PA9T&LCP (GF30%)

RoHS Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准	Helen	SCALE 比例	参考	TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖	Linda	UNIT 單位	MM	.0 ±0.30 .00 ±0.10 ANG. ±	MICRO USB B TYPE WATERPROOF TYPE & OFFSET TYPE
DATE 制表日	2020/5/28	PAGE 張數	1 / 1	SIZE. 紙張尺寸	A4
		REV. 版本	B		5PIN FEMALE PIN FOOT: SMT TYPE
					SHELL FOOT: DIP TYPE GOLD FLASH PLATING
					BLACK COLOR REEL PACKING ROHS
					PART NO. 料號
					C8399-05BFBGBRR