



NOTE :

- CURRENT RATING:
a:TYPE-C: 8.0A MAX
b:USB2.0: 5.0A MAX
- Withstanding Voltage: 100V AC
- TEMPERATURE RANGE: -30 °C ~ 85 °C
- CONTACT RESISTANCE: 40 MILLIONHM MAX
- INSULATION RESISTANCE: 100 MEGOHMS
- INSERTION FORCE : 5N~20N
- UNMATING FORCE: 8N~20N (1~1000次)
6N~20N (10000次之后)
- DURABILITY: 10,000 CYCLES

| 7 | TYPE C MD | HIGH TEMP | BLACK | UL 94V-0 |
|-----|-----------------|-----------------|-------|-------------|
| 6 | CENTER PIECE | STAINLESS STEEL | — | NO Plated |
| 5 | TYPE C TERMINAL | COPPER ALLOY | — | Gold Plated |
| 4 | CLIP | SEE NOTE | — | Ni Plated |
| 3 | USB TERMINAL | COPPER ALLOY | — | Gold Plated |
| 2 | SHELL | SEE NOTE | — | Ni Plated |
| 1 | HOUSING | HIGH TEMP | BLACK | UL 94V-0 |
| NO. | DESCRIPTION | MATERIAL | COLOR | REMARK |

RoHS Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准: Betty

DWG. 製圖: Betty

DATE 制表日: 2020/05/19

SCALE 比例: 參考

UNIT 單位: MM

PAGE 張數: 1 OF 1

30~ ±0.50
10~ 30 ±0.30
~ 10 ±0.15

ANGLES ±2°
GENERAL TOLERANCE UNLESS OTHERWISE NOTED

SIZE 紙張尺寸: A 4

REV. 版次: A

PART NAME 品名: USB Connector Double layer 2 in 1
Type C 14Pin Female+USB A Type 4Pin Female
Shell Material: Copper Alloy Shell Plating: Nickel Plating
Black Color(Material:LCP) Tray Packing ROHS

PART NO. 料號: C8660-01AANXBHR