



Specification

1. Insertion force: 3.5N MAX.
2. Withdrawal force: 8N MIN. INITIAL 8-25N AFTER
3. Rated current: 1.0A
4. Rated voltage: 30V
5. Durability (Life Test) : 5000 Cycles MIN.
6. Voltage resistance: 100V AC MIN.
7. Contact resistance: 30mΩ MAX. INITIAL; 40mΩ MAX AFTER.
8. Insulation resistance: 100MΩ MIN.
9. Working temperature: -30°C TO +80°C
10. Insulator material: LCP UL94V-0
11. Contact material: C2680R-H, GOLD 1u" PLATED
12. Shell material: SUS201/301, MATTE TIN PLATED.

APPD. 核准		SCALE 比例 參考	GENERAL TOLERANCE 0. ±0.35 0.0 ±0.25 0.00 ±0.15 0.0 ±0.5 0.0 ±3	PART NAME 品名 MICRO USB B TYPE 5P FEMALE VERTICAL TYPE PIN FOOT:SMT TYPE, SHELL FOOT:DIP+SMT TYPE WITHOUT LOCATING PEG GOLD FLASH PLATING SHELL:MATTE TIN PLATING PAD+REEL PACKING BLACK COLOR ROHS
DWG. 製圖 Betty				
DATE 制表日 2021/11/11		PAGE 張數 1 OF 2	REV. 版次 A	PART NO. 料號 C8672-05BFCGNBZQR

RoHS Compliant **HSM** 玄茂科技股份有限公司  
HSUAN MAO TECHNOLOGY CO., LTD.

