



加防水圈示意圖

RECOMMENDED P.C.B. LAYOUT
TOLERANCE UNSPECIFIED ±0.05mm

- NOTES:
 1.ELECTRICAL:
 1)CURRENT RATING: 3A MAX.
 2)INSULATION RESISTANCE: 100MΩ MIN;
 3)CONTACT RESISTANCE: 40mΩ MAX;
 4)WITHSTANDING VOLTAGE: 100V AC
 5)OPERATING TEMPERATURE:-30°C TO +85°C.
 2.Mechanical:
 1)Mating Force: 5N~20N
 2)Unmating Force: 8N~20N
 3)Durability: 10,000 cycles
 3.DIMENSIONS MARKED "▼"
 TO BE CHECKED BY Q.C & IPQC.

A5	CC1	B12	GND
A9	VBUS	B9	VBUS
A12	GND	B5	CC2
PIN	SIGNAL NAME	PIN	SIGNAL NAME

6	WATERPROOF RING	SILICONE RUBBER	1	BLACK
5	SHELL	STAINLESS STEEL	1	PLATED NICKEL
4	SHIELDING PLATE	STAINLESS STEEL	1	
3	CONTACT	COPPER ALLOY	6	PLATED GOLD/TIN
2	SHELL HOUSING	LCP+30%GF	1	UL94V-0
1	HOUSING	LCP+30%GF	1	UL94V-0
NO	PARTS	MATERIAL	QTY	FINISHING

RoHS Compliant	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
	APPD. 核准 HELEN	TOLERANCE X' ±2' .X' ±1' .XX ±0.20 .XXX ±0.10
DWG. 製圖 ABBY	SCALE 比例 參考	PART NAME 品名 USB TYPE C WATERPROOF TYPE OFFSET TYPE 6PIN FEMALE PIN FOOT:SMT TYPE NICKEL SHELL:DIP TYPE CONTACT AREA:GOLD 1u" PLATING SOLDER AREA:TIN PLATING BLACK COLOR REEL PACKING ROHS
DATE 制表日 2023/01/16	UNIT 單位 MM	PART NO. 料號 C8690-06CFNBR0R
	PAGE 張數 1 OF 1	