



RATING: DC12V 50mA
 WITHSTAND VOLTAGE: AC250V(50Hz)/min
 CONTACT RESISTANCE: $\leq 30m\Omega$
 INSULATION RESISTANCE: $\geq 100M\Omega$
 TRAVEL TO CLOSURE: $0.15 \pm 0.1mm$
 OPERATION FORCE: $250gf \pm 50gf$
 LIFE TEST: 50,000 cycles

5	TERMINAL	BRASS	4	Ag-PLATED
4	CONTACT	SUS	1	
3	COVER	SUS	1	NATURE
2	CASE	PA66	1	BLACK
1	KNOB	PA66	1	BLACK
NO.	DESCRIPTION	MATERIAL	QTY.	PLATED

APPD. 核准 DWG. 製圖 DATE 制表日 2015/08/31	Betty	SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3° SIZE. 紙張尺寸 A 4 REV. 版次 A	PART NAME 品名 TACT SWITCH SMT TYPE 4.7*4.5mm H=1.7mm OPERATING FORCE: 250gf W/O LOCATING PEG (PITCH: 2.75mm) BUTTON COLOR: BLACK COLOR REEL PACKING ROHS PART NO. 料號 C8708-CNBR0000R
	RoHS Compliant	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.		