



RATING: DC12V 50mA  
 WITHSTAND VOLTAGE: AC250V(50Hz)/min  
 CONTACT RESISTANCE:  $\leq 30m\Omega$   
 INSULATION RESISTANCE:  $\geq 100M\Omega$   
 TRAVEL TO CLOSURE: 0.15mm  
 OPERATION FORCE: 180gf $\pm$ 50gf  
 LIFE TEST: 100,000 cycles

6				
5	TERMINAL	BRASS	4	Ag-PLATED
4	CONTACT	SUS	1	Ag-PLATED
3	KNOB	PA66	1	BLACK
2	COVER	SUS	1	
1	HOUSING	PA66	1	BLACK
NO.	DESCRIPTION	MATERIAL	QTY.	PLATED

APPD. 核准 Betty		TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3°	PART NAME 品名 3.4mm X 3.4mm Tact Switch S.M.T Type H=1.5mm Operating Force:180gf Button Color:Black Color ROHS
DWG. 製圖 Betty	UNIT 單位 M M	SIZE. 紙張尺寸 A 4	PART NO. 料號 C8710-AEBX0000R
DATE 制表日 2015/12/04	PAGE 張數 1 OF 1	REV. 版次 A	

**RoHS Compliant** **HSM 玄茂科技股份有限公司**  
**HSUAN MAO TECHNOLOGY CO., LTD.**