



RATING: DC12V 50mA
 WITHSTAND VOLTAGE: AC250V(50Hz)/min
 CONTACT RESISTANCE: $\leq 30m\Omega$
 INSULATION RESISTANCE: $\geq 100M\Omega$
 TRAVEL TO CLOSURE: $0.25 \pm 0.1mm$
 OPERATION FORCE: $160gf \pm 50gf$
 LIFE TEST: 100,000 cycles

6				
5	TERMINAL	BRASS	4	Ag-PLATED
4	SPRING	Ag2/QSn6.5-0.1	1	
3	HOUSING	PA66	1	BLACK
2	COVER	SUS	1	Ni-PLATED
1	PUSH PLATE	PA66	1	BLACK
NO.	DESCRIPTION	MATERIAL	QTY.	PLATING

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD.
核准
Betty
DATE 制表日
2016/09/30

SCALE
比例 参考
UNIT
單位 M M
PAGE
張數 1 OF 1

TOLERANCE
容許公差
.0 ± 0.30
.00 ± 0.20
ANG. ± 3°
SIZE.
紙張尺寸 A 4
REV.
版次 A

PART NAME 品名
4.5mm X 4.5mm TACT SWITCH SMT TYPE
KONB HEIGHT : 3.8mm OPERATING FORCE:160gf
BUTTON COLOR:BLACK COLOR REEL PACKING ROHS
PART NO.
料號 C8713-TABBR000R