



Specifications

1. Rating: 50mA DC12V
2. Contact resistance: $100m\Omega$
3. Operating force: $160 \pm 50gf$
4. Stroke: $0.25 \pm 0.1mm$
5. Insulation resistance: $100M\Omega$
6. Dielectric strength: 250V 50HZ 1Min.
7. Life: 100,000 Cycles

Material

1. Housing: LCP, Black color
2. Knob: Brass
3. Terminal: Brass, Ag plating
4. Spring: Stainless steel, Ag cladding
5. Cover: Stainless steel
6. Tape: PE

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		TOLERANCE ≥0.5-2 ±0.10 >2-5 ±0.25 >5-10 ±0.30 Ang. ±0.5°	PART NAME 品名 5.2X5.2MM TACT SWITCH SMT TYPE METAL STEM(MATERIAL:BRASS,NO PLATING) H=3.5MM OPERATING FORCE:160gf INSULATOR:LCP REEL PACKING ROHS
DWG. 製圖	Betty	SCALE 比例 參考	PART NO. 料號 C8717-FB0NR000R
DATE 制表日 2020/12/11	UNIT 單位 MM	SIZE. 紙張尺寸 A4	
	PAGE 張數 1 OF 1	REV. 版次 A	