



Specifications

1. Rating: 50mA DC12V
2. Contact resistance: 100mΩ
3. Operating force: 160±50gf
4. Stroke: 0.25±0.1mm
5. Insulation resistance: 100MΩ
6. Dielectric strength: 250V 50HZ 1Min.
7. Life: 100,000 Cycles

Material

1. Housing: LCP, Black color
2. Knob: Brass
3. Terminal: Brass, Ag plating
4. Spring: Stainless steel, Ag cladding
5. Cover: Stainless steel
6. Tape: PE

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例 参考	TOLERANCE	PART NAME 品名
DWG. 製圖		>0.5-2 ±0.10	5.2X5.2MM TACT SWITCH SMT TYPE
DATE 制表日	UNIT 單位	>2-5 ±0.25	METAL STEM(MATERIAL:BRASS,NO PLATING)
2020/12/11	M M	>5-10 ±0.30	H=1.5MM OPERATING FORCE:160gf INSULATOR:LCP
	PAGE 張數	Ang. ±0.5°	REEL PACKING ROHS
	1 OF 1	SIZE. 紙張尺寸	PART NO.
		REV. 版次	料號
		A	C8717-QB0NR000R