



P.C.B. LAYOUT  
(VIEW FROM THE DIRECTION A)

ITEM	DESC	Q'TY	MATERIALS	TREATMENT
1	COVER	1	STAINLESS STEEL	NONE
2	TERMINAL	1	PHOSPHOR BRONZE	WITH SILVER PLATING 0.5u"
3	SPRING	1	PHOSPHOR BRONZE	WITH SILVER PLATING 0.5u"
4	STEM	1	HIGH-TEMP THERMOPLASTIC LCP	MOLDED BLACK
5	BASE	1	HIGH-TEMP THERMOPLASTIC LCP	MOLDED BLACK

RoHS  
Compliant

**HSM** 玄茂科技股份有限公司  
**HSUAN MAO TECHNOLOGY CO., LTD.**

APPD. 核准		TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖	SCALE 比例	.0 ± 0.30 .00 ± 0.20 ANG. ± 3°	2.8X3.5mm DETECTOR SWITCH
DATE 制表日	UNIT 單位	SIZE. 紙張尺寸	4PIN SMT TYPE WITHOUT POST
2018/08/22	M M	A 4	BLACK COLOR REEL PACKING ROHS
	PAGE 張數	REV. 版次	PART NO.
	1 OF 1	A	料號 C8718-04NBR0000R

ON STARTING POSITION  
CONTACT RESISTANCE, OPERATION  
FORCE MEASURE POSITION

TOTAL TORAVEL

CIRCUIT