


Circuit Diagram



- NOTE:
1. Genreal tolerances  $\pm 0.2\text{mm}$ .
  2. Solder thickness :  $0.10\text{mm}$
- Specifications :
1. Rating :  $50\text{mA, DC } 32\text{V Max.}$   
 $1\text{mA, DC } 20\text{mV Min.}$
  2. Inital contact resistance :  $100\text{m}\Omega \text{ Max.}$
  3. Insulation resistance :  $\text{DC } 100\text{V} - 10\text{M}\Omega \text{ Min.}$
  4. Dielectric strength :  $\text{AC } 250\text{V} - 1 \text{ minute.}$
  5. Operating force :  $160/200/350\text{gf}$
  6. Operaing life : *see product specification*

Part NO.	$\phi(A)$	High(B)
C8730-BXDR0000R	$\phi 2.9$	3.5
C8730-EXDR0000R	$\phi 2.7$	5.2

ITEM	DESC	Q'TY	METERIALS	TREATMENT
1	STEM	1	SILICONE RUBBER	-
2	COVER	1	STAINLESS STEEL	NONE
3	CONTACT	1	STAINLESS STEEL	WITH SILVER PLATING
4	TERMINAL	1	BRASS	WITH SILVER PLATING
5	BASE	1	HIGH-TEMP THERMOPLASITC LCP	MOLDED BLACK

**RoHS Compliant**

**HSM 玄茂科技股份有限公司**

**HSUAN MAO TECHNOLOGY CO., LTD.**

APPD. 核准 DWG. 製圖 DATE 制表日 <b>Hedy</b> 2019/01/29	<p>SCALE 比例 參考</p> <p>UNIT 單位 MM</p> <p>PAGE 張數 1 / 1</p>	TOLERANCE 容許公差 $.0 \pm$ $.00 \pm$ $\text{ANG.} \pm$	PART NAME 品名 6.2X6.2mm IP67 WASHABLE TYPE TACT SWITCH SMT TYPE KONB HEIGHT:3.5mm OR 5.2mm REEL PACKING ROHS PART NO. 料號 <b>C8730-(B,E)XDR0000R</b>
--	---	--	--

