



Notes:

1. Material:
  - 1.1 Insulator: PA66 UL94V-0, Black Color.
  - 1.2 Contact: H62
2. Surface process:
  - 2.1 Terminal: Nickel Plating, 30u" Min.
3. Specification:
  - 3.1 Contact resistance:  $\leq 500\text{m}\Omega$
  - 3.2 Insulation resistance:  $\geq 1000\text{M}\Omega$
  - 3.3 Voltage resistance: 500 Vr.m.s, 1mA, 60s.
  - 3.4 Insertion force:  $\leq 45\text{N}(4.5\text{kgf})$
  - 3.5 Durability (Life Test) :  $\geq 3000$  Cycles
  - 3.6 Soldering heat resistance temperature:  $250^{\circ}\text{C} \pm 5^{\circ}\text{C}$ , 10s.
4. Packing: 100pcs/Bag

RoHS Compliant		<b>玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准	 SCALE 比例 参考	TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖		.0 ± 0.30 .00 ± 0.20 ANG. ± 3°	POWER SOCKET CONNECTOR SOLDER TYPE 2+6PIN MALE NICKEL PLATING MATERIAL:PA66 UL94V-0 BLACK COLOR BAG PACKING ROHS
DATE 制表日	UNIT 單位	SIZE. 紙張尺寸	PART NO.
2021/12/22	M M	A 4	料號 C8980-08MNAB00R
	PAGE 張數	REV. 版次	
	1 OF 1	A	

Betty