



PIN OUT :

RJ45-8P	PCB
	1 -- NC
1 -----	2
2 -----	3
3 -----	4
4 -----	5
5 -----	6
6 -----	7
7 -----	8
8 -----	10
	11 -- NC
	Shield --- 12 -- GND

Note :
Waterproof Rate : IP 68
UV Resist

Specification:
 Current Rating : 1.5A
 Voltage Rating :125VAC
 Operating Temp:-20°C ~ +85°C
 Insulation Resistance:1000MΩ
 Dielectric Withstanding Voltage:1KV
 Contact Resistance:40mΩ

9	Rope	EPDM Black
8	Dust Cover	EPDM Black
7	Sealing Nut	Nylon + GF Black -40 ~ +105°C
6	Housing	Nylon + GF Black -40 ~ +105°C
5	Wire Clip	Nylon Black
4	Gasket	EPDM Black
3	PCB	FR-4
2	RJ45	Shielded Jack 8Pin
1	Housing	Nylon + GF Black -40 ~ +105°C

RoHS Compliant **HSM 玄茂科技股份有限公司**
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准		TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖	Betty	SCALE 比例 參考	WATERPROOF TYPE IP68 TYPE MODULAR JACK 10P8C GOLD 6U" PLATING TO P.C BOARD ASSEMBLY TYPE W/O POWER PIN WITH DUST COVER BLACK COLOR ROHS
DATE 制表日	2020/01/20	UNIT 單位 M M	PART NO.
		PAGE 張數 1 OF 1	料號 C9403-08KNB000R
		REV. 版次 A	