



SPECIFICATIONS

Current Rating : 1.5AMP
 Operation Temperature: -40° C to +105° C
 Contact Resistance : 20m Ω Max.
 Insulation Resistance: 1000M Ω Min.
 Withstanding Voltage : AC 500V
 Insulator Material : Polyester (UL94V-0)
 Standard: PA6T
 Contact Material : Brass
 Contact plating : Au or Sn

Dimensions list

Contacts Per row	Dimensions	
	A	B
10	26.00	8.00
14	30.00	12.0
16	32.00	14.0
20	36.00	18.0
26	42.00	24.0
30	46.00	28.0
40	56.00	38.0
44	60.00	42.0
50	66.00	48.0

RoHS Compliant		玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Hedy	SCALE 比例 參考	TOLERANCE 容許公差 X: ±0.80 X*: ±1* X.X: ±0.20 X.X*: ±0.05* X.XXX: ±0.15 X.XX*: ±0.05*	PART NAME 品名 2.0x2.0mm SHROUDED HEADER SMT TYPE XXP SHORT LATCH GOLD FLASH PLATING BLACK COLOR ROHS LOW-LEAD
DWG. 製圖 Yumi	UNIT 單位 MM	SIZE 紙張尺寸 A 4	PART NO. 料號 C9000-XXDGB000R
DATE 製表日 2010/11/29	PAGE 張數 1 OF 1	REV. 版次 A	