



1. MATERIAL :
- 1-1. HOUSING : PBT ; COLOR : BLACK
 - 1-2. CONTACT : BRASS.
 - 1-3. SHELL : BRASS
 - 1-4. O-RING : NBR ; COLOR : BLACK
 - 1-5. NUT : BRASS.
2. FINISH :
- 2-1. CONTACT : 10 MICRO INCHES MIN. GOLD PLATING
 - 2-2. SHELL : NICKEL PLATED.
 - 2-3. NUT : NICKEL PLATED.
3. ELECTRICAL SPECIFICATION :
- 3-1. Rated current : 4A
 - 3-2. Rated voltage : 60V
 - 3-3. Water proof : IP67
 - 3-4. INSULATION RESISTANCE : 1000MΩ MIN
 - 3-5. DIELECTRIC WITHSTANDING VOLTAGE : 800V
 - 3-6. CONTACT RESISTANCE : < 10mΩ
4. Environmental :
- 4-1. Operation Temperature : -20℃~85℃

RoHS Compliant		玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	 SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE	PART NAME 品名
DWG. 製圖 Betty		.x ±0.20 .xx ±0.10 .xxx ±0.05 .xxxx ±0.03 ANGLA ±1°	M8 XXPIN MALE 180° SOLDER TYPE IP67 WATERPROOF TYPE FRONT LOCK M8*1.0mm GOLD 10U" PLATING BLACK COLOR ROHS
DATE 制表日 2020/04/20		REV. 版次 A	PART NO. 料號 C9321-XXMABB00R

4P	3P	2P