



1. MATERIAL :
  - 1-1. HOUSING : PBT UL94V-0 ; COLOR : BLACK
  - 1-2. CONTACT : BRASS
  - 1-3. SHELL : BRASS
  - 1-4. WASHER : BRASS
  - 1-5. NUT : BRASS
  - 1-6. O-RING : EPDM ; COLOR : BLACK
2. FINISH :
  - 2-1. CONTACT : SEE TABLE A
  - 2-2. SHELL : SEE TABLE A
  - 2-3. WASHER : NICKET PLATING
  - 2-4. NUT : SEE TABLE A
3. ELETRICAL SPECICATION :
  - 3-1. Rated current : 4A
  - 3-2. Rated voltage : 60V
  - 3-3. Water proof : IP67
4. Environmental :
  - 4-1. Operation Temperature : -40℃~85℃

TABLE A/表A

	4P	3P	2P
C9322-02MBBB00R			
C9322-03MBGB00R			
C9322-03MBBB00R			
C9322-04MBGB00R			
C9322-04MBBB00R			
P/N	SHELL & NUT FINISH		CONTACT FINISH

RoHS Compliant	<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
	APPD. 核准 BETTY	TOLERANCE × ±0.20 .xx ±0.10 .xxx ±0.05 .xxxx ±0.03 ANGULA ±1°
DWG. 製圖 ABBY	SCALE 比例 參考	PART NAME 品名 M8 XXPIN MALE 180° SOLDER TYPE IP67 WATERPROOF TYPE FRONT LOCK M9*1.0mm BLACK COLOR ROHS
DATE 制表日 2022/10/07	UNIT 單位 MM	PART NO. 料號 C9322-XXMBXB00R
	PAGE 張數 1 OF 1	REV. 版次 B