



NO.	NAME	MATERIAL	FINISH	Q'TY
1	PIN TERM.	BRASS T:0.4	TIN PLATED	1
2	SLEEVE TERM.	PHOS. BRONZE T:0.25	TIN PLATED	1
3	BREAK TERM.	BRASS T:0.4	TIN PLATED	1
4	CENTER PIN	BRASS ϕ 2.0	NICKEL PLATED	1
5	HOUSING	PBT G.F.	BLACK	1
6	BOTTOM COVER	PBT G.F.	BLACK	1

Specification:

Contact Resistance: 30m Ohm Max. At AC 100mA Max .1KHz
 Insulation Resistance: 100M Ohm Min. At 500V DC
 Rated Voltage And Current: DC12V. 2A Max; AC 100V. 1A Max
 Dielectric Withstanding Voltage: 500V AC for 1 Minute
 Insertion Force: 3.0Kg Maximum.
 Extraction Force: 0.3Kg Minimum.

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准		TOLERANCE X. \pm 0.38 X \pm 0.25 .XX \pm 0.13 .XXX \pm 0.05
DWG. 製圖	SCALE 比例 參考	SIZE. 紙張尺寸 A 4
DATE 制表日	UNIT 單位 MM	REV. 版次 A
2014/11/20	PAGE 張數 1 OF 1	

PART NAME 品名
DC POWER JACK ϕ 2.0mm
STRAIGHT NICKEL PLATED
BLACK INSULATOR ROHS

PART NO.
料號 C9739-CCSNB000R